

Cabi-lite



Profile Heat Sink	Dimensions	Mounting Accessories	Watt [MAX]
			19.2 W/M

Specifications

Main Features

PARAMETERS	DESCRIPTION
LED PACKAGE	2835, 3/5 SDCM, LM80 PART
CRI	80-85 Ra, 90-95 Ra
CCT/COLOR	2300~8000*
DIFFUSER	Frosted [Sliding type, 0.3 mm]
END CAPS	Alu
Mounting clips	Alu
V in	12 v dc
DIMENSIONS	17.80 mm W X 15.80 mm H
CUTTABLE LENGTH	24.75 mm
DRIVER	Non-integrated

- 120 LED Per Meter
- Choose from 4.8 to 19.2 watts
- Powered by BRIDGELUX
- Constant voltage
- Finishing: Silver Anodized
- 12 V DC
- IP Rating: IP-44
- MOQ: 10 M

* White: 2300 K, 2700 K, 3000 K, 3500 K, 4000 K, 5000 K, 5500 K, 6000 K, 6500 K, 8000 K.

LM -80 APPROVED

30,000 WORK HOURS

1 BIN PROCESSING

Customization parameters:

❖ STANDARD SIZES : -	500 MM	1000 MM	2000 MM	CUSTOM SIZE
❖ STANDARD WATTAGES : -	4.8W / M	7.2W/M	9.6W/M	11.52W/M

PCB specifications:

- Material: FR4 - RIGID PCB, 1.6 mm thickness
- Width: 10 mm width Cuttable 24.75 mm
- V in: 12V
- LED: 2835, 120 LED/m, 3 LED series

24.75 mm

Applications

Specialized Display Counter Light with Different Lenses



Optional with 100 mm male / female self-locking connector