




Glowstick



| Profile Heat Sink  | Dimensions  | Mounting Clips   | Watt [MAX] |
|--|---|--|------------|
|  |  |  | 14.40 W/M  |

Specifications

Main Features

| PARAMETERS      | DESCRIPTION                     |
|-----------------|---------------------------------|
| LED PACKAGE     | 2835, 3/5 SDCM, LM80 PART       |
| CRI             | 80-85 Ra, 90-95 Ra              |
| CCT/COLOR       | 2300~8000*, R,G,B,A,P,C,Y,F,O** |
| DIFFUSER        | Opal ( press fit)               |
| END CAPS        | Plastic                         |
| Mounting clips  | S.S.                            |
| V in            | 24 v dc                         |
| DIMENSIONS      | 10.00 mm W X 13.00 mm H         |
| CUTTABLE LENGTH | 49.50 mm                        |
| DRIVER          | Non-integrated                  |

- 120 LED Per Meter
- Choose from 4.8 to 14.40 watts
- Powered by BRIDGELUX
- Constant voltage
- Finishing: Silver Anodized
- 24 V DC
- IP Rating: IP-20
- MOQ: 10 M

\* White: 2300 K, 2700 K, 3000 K, 3500 K, 4000 K, 5000 K, 5500 K, 6000 K, 6500 K, 8000 K.

\*\* RGBAPSYFO: - Red, Green Blue, Amber, Pink, Sky-blue, Yellow, Flame, Orange

LM -80 APPROVED

30,000 WORK HOURS


1 BIN PROCESSING

Customization parameters:

|                        |          |         |         |             |
|------------------------|----------|---------|---------|-------------|
| ❖ STANDARD SIZES: -    | 500 MM   | 1000 MM | 2000 MM | CUSTOM SIZE |
| ❖ STANDARD WATTAGES: - | 4.8W / M | 7.2W/M  | 9.6W/M  | 14.40 W/M   |

PCB specifications:

- Material: FR4 - RIGID PCB, 1.6 mm thickness
- Width: 8 mm width Cuttable 49.50 mm
- V in: 24V dc
- LED: 2835, 120 LED/m, 6 LED series



Applications

Under Cabinet, Kitchen, Furniture, Decorative, Architectural Lighting, etc.



Optional with 100 mm male / female self-locking connector