




Snow-lite



| Profile Heat Sink | Dimensions | Mounting Clips | Watt [MAX] |
|--|---|--|------------|
|  |  |  | 28.8 W/M |

Specifications

Main Features

| PARAMETERS | DESCRIPTION |
|-----------------|---------------------------------|
| LED PACKAGE | 2835, 3/5 SDCM, LM80 PART |
| CRI | 80-85 Ra, 90-95 Ra |
| CCT/COLOR | 2300~8000*, R,G,B,A,P,C,Y,F,O** |
| DIFFUSER | Opal (Press fit) |
| END CAPS | Alu |
| Mounting clips | Alu Spring clip |
| V in | 24 v dc |
| DIMENSIONS | 65.00 mm W X 32.00 mm H |
| CUTTABLE LENGTH | 31 mm |
| DRIVER | Non-integrated |

| | |
|----------------------------------|--|
| ▪ 192 LED Per Meter (Customized) | ▪ Choose from 9.6 to 28.8 watts (Customized) |
| ▪ Powered by BRIDGELUX | ▪ Constant voltage |
| ▪ Finishing: Silver Anodized | ▪ 24 V DC |

* White: 2300 K, 2700 K, 3000 K, 3500 K, 4000 K, 5000 K, 5500 K, 6000 K, 6500 K, 8000 K.

** RGBAPSYFO: - Red, Green Blue, Amber, Pink, Sky-blue, Yellow, Flame, Orange

LM -80 APPROVED

30,000 WORK HOURS


1 BIN PROCESSING

Customization parameters:

| | | | | |
|------------------------|----------|----------|----------|-------------|
| ❖ STANDARD SIZES: - | 500 MM | 1000 MM | 2000 MM | CUSTOM SIZE |
| ❖ STANDARD WATTAGES: - | 9.6W / M | 14.4 W/M | 19.2 W/M | 28.8W/M |

PCB specifications:

- Material: ALU- RIGID PCB, 1.6 mm thickness
- Width: 25 mm width Cuttable 31 mm
- V in: 24V dc
- LED: 2835, 192 LED/m, 6 LED series



Applications

Commercial Linear Lighting for Recessed Applications, etc.



Optional with 100 mm male / female self-locking connector