

Wash-line

Profile Heat Sink	Dimensions	Mounting Clips	Watt [MAX]
			27 W/M

Specifications

Main Features

PARAMETERS	DESCRIPTION
LED PACKAGE	2835, 3/5 SDCM, LM80 PART
CRI	80-85 Ra, 90-95 Ra
CCT/COLOR	3000K/ 4000/ 5000K*
DIFFUSER	15°, 30° lens with reflector
END CAPS	Alu
Mounting clips	Spring clip
V in	45 v dc
DIMENSIONS	35.00 mm W X 70.00 mm H
CUTTABLE LENGTH	N/A
DRIVER	Non-integrated

- 45 LED Per Meter (Customized)
- 27 watts (Customized)
- Powered by BRIDGELUX
- Constant voltage
- Finishing: Silver Anodized
- 45 V DC
- IP Rating: IP-44
- MOQ: 5 nos

* White: 3000 K, 3500 K, 4000 K, 5000 K, 5500 K,

LM -80 APPROVED

30,000 WORK HOURS

1 BIN PROCESSING

Customization parameters:

❖ STANDARD SIZES :-	600 MM	1200 MM	1800 MM	2400 MM	CUSTOM SIZES
❖ STANDARD WATTAGES :-	18 W	36 W	54 W	72 W	AS PER

PCB specifications:

- Material: ALU - RIGID PCB, 1.6 mm thickness
- Width: 26 mm
- V in: 45 V dc
- LED: 3535, 45 LED/m, 15 LED series X 3 Parallel

Applications

Economy surface Lighting, Under cabinet, kitchen, furniture, small coves, mirrors etc.



Optional with 100 mm Male / female self-locking connector